



Cover



Strain Relief

ELECTRICAL:

CURRENT: 1 Amp
CONTACT RESISTANCE: < 30mΩ
INSULATOR RESISTANCE: > 1000MΩ
DIELECTRIC WITHSTANDING VOLTAGE: 500VAC FOR 1 MIN.
OPERATING TEMPERATURE: -55° C TO +105° C

MATERIAL:

INSULATOR: PBT & 30% GLASS FIBER (UL94V-0)
CONTACT: BRASS
CONTACT PLATING: OPTIONAL GOLD OR TIN ALL OVER NICKEL

MECHANICAL:

WIRE SIZE: AWG 26 ~ AWG 28

DIMENSION(mm)

DIM POS	A	B	C	D
9	16.00	24.99	30.50	10.16
15	24.27	33.32	39.00	17.78
25	38.22	47.04	53.08	30.48
37	54.65	63.50	69.25	45.72

HOW TO ORDER:

A	2	0	1	-	X	X	X	3	-	X	0	X	-	Z
CONTACT TYPE: 1 - FEMALE			STRAIN RELIEF: 0 - w/STRAIN RELIEF 1 - w/OUT STRAIN RELIEF			MOUNTING OPTION: 1 - 3.05mm HOLE 2 - 4-40 THREADED INSERT			RoHS COMPLIANT					
NUMBER OF CONTACTS: 09, 15, 25, 37			SHELL PLATING: 1 - TIN PLATED 2 - ZINC PLATED 3 - ALL PLASTIC 4 - NICKEL PLATED			SELECTIVE PLATING: 1 - Au FLASH CONTACT AREA/TIN TAIL 9 - 15u" Au CONTACT AREA/TIN TAIL A - 30u" Au CONTACT AREA/TIN TAIL								

Rev	Drawn	Checked	Approved	Date
0	A.M.	S.M.	S.M.	11/20/03
A	B.S.	S.M.	S.M.	6/20/07

SCALE:n/a IDC D-Subminiature Female Connector; 9,15,25 and 37 Position, All Plastic

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- ANGLE +/- UNIT: mm P/N: A201-XXX3-X0X-Z