




MEETS IEEE 802.3 SPECIFICATION

LED SCHEMATIC



MATES WITH PLUG CONFORMING
TO FCC PART 68, SUBPART F.



RECOMMENDED PCB LAYOUT

HOW TO ORDER:

A 3 0 1 1 - A A 1 1 - 0 2 X - G Y T7 - Z
LED 1: LED 2: RoHS COMPLIANT


SELECTIVE PLATING:

6 - 6u" Au CONTACT AREA/TIN TAIL
7 - 10u" Au CONTACT AREA/TIN TAIL
8 - 15u" Au CONTACT AREA/TIN TAIL
9 - 30u" Au CONTACT AREA/TIN TAIL

W/ TRANSFORMER:

T7 - Type 7 Transformer

Insertion Loss	1 ~ 100 Mhz.	- 1 db Max.
Return Loss	1 ~ 30 Mhz.	- 18 db Min.
	30 ~ 60 Mhz.	- 13 db Min.
	60 ~ 80 Mhz.	- 10 db Min.
	80 ~ 100 Mhz.	- 10 db Min.
Crosstalk	1.0 ~ 100 Mhz.	- 30 db Min.
Common Mode Rejection	1 ~ 100 Mhz.	- 30 db Min.
Hi-Pot	2250 VDC @ 60 Seconds	
DC Current /Voltage Rating	0.1 A Max@48 VDC (Continuous)	
OCL	350 uH Min@100 KHz/0.1V with 8mA DC Bias	
Turns Ratio (+/- 2%)	Tx 1Ct:1Ct Rx=1Ct:1Ct	



SCHEMATIC DIAGRAM

ELECTRICAL:

VOLTAGE RATING: 120V AC

CURRENT RATING: 1.5A Min.

CONTACT RESISTANCE:

< 20 Milliohm Max.

INSULATION RESISTANCE:

> 500 Megaohm Min.

DIELECTRIC WITHSTANDING VOLTAGE:

1000V (rms) AC for 1 Minute Min.

OPERATING TEMPERATURE: 0° C to +70° C

ISOLATION VOLTAGE :1500Vrms

MATERIAL:

INSULATOR: Thermolastic Glass Filled (UL94V-0)

CONTACT: 0.35mm Thickness Phosphor Bronze

CONTACT PLATING: Gold Plating over Nickel

SOLDERING TEMP MAX: 265° C for 5 Sec. Max.

MECHANICAL:

DURABILITY: 500 Mating Cycles Min.

Rev	Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.
0	B.S.	S.M.	S.M.	9/16/15	
					1000 BASE-TX RJ45 JACK, GIGABIT; w/LED's ;SINGLE PORT
					OFFSET 2.80 mm; SHIELDED, ,
SCALE: N/A					
TOL. DEC.	.X +/-	.XX +/- 0.25	.XXX +/- 0.15	ANGLE +0.45/-0.15	UNIT: mm
P/N: A3011- AA11-02X-GYT7-Z					