







HOW TO ORDER:

B 0 6 1 - X X 4 2 - 2 0 X - Z

NUMBER OF CONTACTS:

04 thru 80

DEFINITION:

4 - RIGHT ANGLE w/POLARIZING KEY

NUMBER OF ROWS:

2 - TWO

CONTACT STYLE:

2 - TUNING FORK

HOUSING DIMENSIONS:

Height - 8.50mm

Contact Tail - 3.15mm

PLATING OVERALL:

RoHS

COMPLIANT

0 - FULL TIN

1 - FULL Au

3 - 10u" Au

4 - 15u" Au

5 - 30u" Au

SELECTIVE PLATING:

6 - Au CONTACT AREA/TIN TAIL

7 - 10u" Au CONTACT AREA/TIN TAIL

8 - 15u" Au CONTACT AREA/TIN TAIL

9 - 30u" Au CONTACT AREA/TIN TAIL

ELECTRICAL:

CURRENT: 3A

CONTACT RESISTANCE: 20mΩ Max.

INSULATOR RESISTANCE: 5000MΩ Min.

DIELECTRIC WITHSTANDING VOLTAGE: 500VAC FOR 1 MIN.

OPERATING TEMPERATURE: -40° C TO +105° C

MATERIAL:

INSULATOR: GLASS FILLED POLYESTER (UL94V-0)

CONTACT: COPPER ALLOY

Rev		Drawn	Checked	Approved	Date
0	Issued	A.M.	S.M.	S.M.	08/25/03
A	Revised for RoHS Compliance	B.S.	S.M.	S.M.	12/15/06

SCALE:n/a

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- 0.15 ANGLE +/- 5° UNIT: mm

SMP TECHNOLOGY, INC.

Receptacle Assembly, 2.54mm Pitch, Double Row w/Polarization, Right Angle

Tuning Fork Contact, Thru Hole

SERIES: B061

Pg: 1