





HOW TO ORDER:

B 0 6 7 - X X X 2 - 6 0 X X - Z

OF CONTACTS:
04 thru 84

CONTACT TAIL OPTIONS:

2 - SURFACE MOUNT w/POST
3 - SURFACE MOUNT w/OUT POST

BODY HEIGHT:
6 - 4.3mm

HOUSING OPTION:

2 - DOUBLE ROW TOP ENTRY

PLATING OVERALL:

0 - FULL TIN

1 - FULL Au FLASH

3 - 10u" Au

4 - 15u" Au

5 - 30u" Au

PACKAGING:

0 - Tube

1 - Tube w/ Cap

2 - Tape & Reel w/ Cap

SELECTIVE PLATING:

6 - Au FLASH CONTACT AREA/TIN TAIL

7 - 10u" Au CONTACT AREA/TIN TAIL

8 - 15u" Au CONTACT AREA/TIN TAIL

9 - 30u" Au CONTACT AREA/TIN TAIL

RoHS
COMPLIANT

ELECTRICAL:

CURRENT: 1A

CONTACT RESISTANCE: 20 milliohms Max.

INSULATOR RESISTANCE: 5000 Megohms Min.

DIELECTRIC WITHSTANDING VOLTAGE: 500VAC For 1 MIN.

OPERATING TEMPERATURE: -40°C to +105°C

MAX PROCESSING TEMPERATURE: 230° For 30 ~ 60 Sec. (260° For 10 Sec.)

MATERIAL:

INSULATOR: Polyester, UL 94V-0 ; Nylon-6T

CONTACT: Phosphor Bronze

CONTACT PLATING: Full Gold, Full Tin, Selective Plating

Rev	Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.	
0	Issued	A.M.	S.M.	S.M.	08/08/03	
A	Revised for RoHS Compliance	B.S.	S.M.	S.M.	12/15/06	
B	Added Packaging	B.S.	S.M.	S.M.	04/25/19	
SCALE:n/a					Top Entry, With or Without Mounting Posts, 4.3mm Height	
TOL. DEC.	.X +/- 0.35	.XX +/- 0.25	.XXX +/- 0.15	ANGLE +/- 5°	UNIT: mm	SERIES: B067
						Pg: 1

Receptacle Assembly, 2.00mm Pitch, Double Row, Surface Mount