




HOW TO ORDER:

B 0 7 0 - X X 3 0 - 2 8 X - Z

NUMBER OF CONTACTS:

04 thru 40

DEFINITION:

3 - STRAIGHT DOUBLE ROW

BODY OPTION:

0 - STANDARD

HEIGHT OPTIONS:

8 - 11.39mm

CONTACT STYLE:

2 - TUNING FORK

PLATING OVERALL:

0 - FULL TIN
1 - FULL Au
3 - 10u" Au
4 - 15u" Au
5 - 30u" Au

SELECTIVE PLATING:

6 - Au CONTACT AREA/TIN TAIL
7 - 10u" Au CONTACT AREA/TIN TAIL
8 - 15u" Au CONTACT AREA/TIN TAIL
9 - 30u" Au CONTACT AREA/TIN TAIL

**RoHS
COMPLIANT**

ELECTRICAL:

CURRENT: 1.5A
CONTACT RESISTANCE: 20 milliohms Max.
INSULATOR RESISTANCE: 5000 Megohms Min.
DIELECTRIC WITHSTANDING VOLTAGE: 500VAC FOR 1 MIN.
OPERATING TEMPERATURE: -40° C TO +105° C

MATERIAL:

INSULATOR: GLASS FILLED POLYESTER (UL94V-0) ; NYLON 6T
CONTACT: COPPER ALLOY

Rev		Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.
0	Issued	A.M.	S.M.	S.M.	07/29/03	
A	Revised for RoHS Compliance	B.S.	S.M.	S.M.	2/22/07	
						Receptacle Assembly, 2.00mm Pitch, Vertical, Tuning Fork Contact
SCALE:n/a						Double Row, 11.39mm Height
TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- 0.15 ANGLE +/- 5° UNIT: mm						SERIES: B070
						Pg: 1