







PCB LAYOUT
(BOTTOM VIEW)

TERMINAL TAB (1)

GROUNDING TAB (2)



ELECTRICAL:

CURRENT: 100VAC 1A MAX. / 12VDC 2A MAX.
CONTACT RESISTANCE: 30mΩ Max.
INSULATOR RESISTANCE: 50MΩ Min. AT 250VDC

MATERIAL:

INSULATOR: THERMOPLASTIC PBT (UL94V-0)
CONTACT: PHOSPHOR BRONZE
SHIELD: COPPER ALLOY

MECHANICAL:

INSERTION FORCE: 4.5Kg Max.
WITHDRAWAL FORCE: 0.9~3Kg

HOW TO ORDER:

D **0** **0** **7** - **0** **4** **6** **1** - **2** **0** **X** - **Z**

NUMBER OF CONTACTS:
04 CONTACTS

GROUNDING TABS:
1 - STRAIGHT TYPE

TERMINAL TYPE:
2 - SNAP IN FIT

SHIELDING:
6 - PANEL MOUNT
w/M3 SCREW ATTACHMENT

RoHS COMPLIANT

SELECTIVE PLATING:

0 - Au FLASH CONTACT AREA/TIN TAIL
1 - 15u" Au CONTACT AREA/TIN TAIL
2 - 30u" Au CONTACT AREA/TIN TAIL

Rev		Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.
0	Issued	D.H.	S.M.	S.M.	03/03/04	
A	Revised for RoHS Compliance	B.S.	S.M.	S.M.	07/30/08	Mini Din Connector, 4 Position, Fully Shielded w/Panel Mount Screw Attachment (M3), Straight Grounding Tabs, Snap Fit Terminal Tab
TOL. DEC. X. +/- 0.5 X.X +/- 0.3 X.XX +/- 0.15 ANGLE +/- 3° UNIT: mm						P/N: D007-0461-20X-Z