










Recommended PCB Layout
(BOTTOM VIEW)



SEC A-A



HOW TO ORDER:

P 0 0 2 - 3

CENTER PIN DIAMETER:

3 - 1.3mm

7 C 0 - 2

PCB MOUNTING OPTIONS:

2 - SOLDER TAIL (Spring Tab)
RETENTION TAIL

2 0 - Z

PACKAGING:

2 - TUBE

RoHS
COMPLIANT

MECHANICAL:

DURABILITY: 500 Cycles (Insertion & Withdrawl)

ELECTRICAL:

CONTACT RESISTANCE:

BEFORE DURABILITY TEST

BETWEEN TERMINALS: 30 MILLIOHMS Max.

PLUG TO CONTACTS: 50 MILLIOHMS Max.

AFTER DURABILITY TEST

BETWEEN TERMINALS: 60 MILLIOHMS Max.

PLUG TO CONTACTS: 100 MILLIOHMS Max.

RATED VOLTAGE: 24V DC.

RATED CURRENT: 2.5 amps.

INSULATOR RESISTANCE: > 100 Megohms Min. At 500 VDC.

OPERATING TEMPERATURE: -25°C TO +85°C

MATERIAL:

INSULATOR: PBT (UL94V-0)

SIGNAL CONTACT: COPPER ALLOY, TIN PLATED

GROUND CONTACT: COPPER ALLOY, TIN PLATED

TERMINAL: COPPER ALLOY, TIN PLATED

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	04/28/11

SMP TECHNOLOGY, INC.
DC Power Connector with Green LED, 1.3mm Ø Pin