


CONTACT ARRANGEMENT 7W2

SEE PAGE 3 FOR OTHER CONTACT ARRANGEMENTS

Shell Size	A ± 0.20mm	B ± 0.15mm	C ± 0.20mm	D ± 0.20mm	E ± 0.20mm	F ± 0.20mm	G ± 0.20mm	H ± 0.15mm
9	30.8	25	16.9	12.5	8.3	19.25	6.1	4.1
15	39.2	33.3	25.25	12.5	8.3	27.7	6.1	4.1
25	53.05	47.05	38.95	12.5	8.3	41.2	6.1	4.1
37	69.4	63.5	55.4	12.5	8.3	57.5	6.1	4.1
50	67	61	52.8	15.3	11.15	55	6.1	4.1



Footprint (I)	J
9.4	2.54
7.2	2.84

10	11	12	15	16	17	18

High Power Contact Current Rating: 10,20,30,40 AMPS
High Power Contact Resistance: 2.7 Milliohms MAX.
Dielectric Withstanding Voltage: 1000 VAC For 1 Minute
Insulation Resistance: 5000 Megaohms


<u>P</u>	X	3	X	0	-	X	X	X	X	-	X	X	X	X	X	X	0	-	Z
<u>POWER CONTACT</u>			<u>ORIENTATION / FOOTPRINT</u>								<u>MOUNTING OPTION</u>								<u>RoHS COMPLIANT</u>
3 - 10 AMP 4 - 20 AMP 5 - 30 AMP 6 - 40 AMP			1 - Right Angle PCB Mount 9.4 Ft. Print 5 - Right Angle PCB Mount 7.2 Ft. Print								See Table 1								
	<u>SIGNAL CONTACT</u>					<u>CONTACT ARRANGEMENT</u>							<u>SIGNAL CONTACT PLATING</u>	<u>POWER CONTACT PLATING</u>					<u>INSULATOR COLOR</u>
	3 - Male Signal & Female Power					<u>SEE PAGE 3</u> Example: 2W2 = 02W2 Arrangement 7W2 Shown Above ⁰							1 - Full Au Flash 2 - 15 u"Au Over Ni 3 - 30 u"Au Over Ni 4 - 50 u"Au Over Ni						1 - Black 2 - White 3 - Green 4 - Blue

Rev		Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC. Combo Power + Signal D - Sub Connector; Right Angle ; Male Signal Pin P/N: PX3X0-XXXX-XXXXX0-Z
0	Issued	B.S.	S.M.	S.M.	11/23/10	
TOL. DEC. .X +/- 0.3 .XX +/- 0.20 .XXX +/- 0.10 ANGLE +/- 3° UNIT: mm						Pg: 1 of 4


MOUNTING OPTIONS

POWER / COAX COMBO SERIES


MOUNTING OPTION 10:
3.05MM DIAMETER MOUNTING HOLE




MOUNTING OPTION 11:
RIVETED 4-40 SCREW LOCK ON
BACK SIDE OF SHELL




MOUNTING OPTION 12:
RIVETED 4-40 SCREW LOCK ON
FRONT SIDE OF SHELL




MOUNTING OPTION 13:
RIVETED 4-40 SCREW LOCK ON
BACK SIDE OF SHELL




MOUNTING OPTION 15:
4-40 THREADED INSERT W / 4-40
JACKSCREW ATTACHED
WITH BOARD LOCK




MOUNTING OPTION 16:
4-40 THREADED INSERT WITH
BRACKET (3.20 Ø) MTG. HOLE)



MOUNTING OPTION 17:
4-40 TREADED INSERT WITH
BRACKET WITH BOARD
LOCK / BAKELIGHT



MOUNTING OPTION 18:
4-40 THREADED INSERT
WITH BOARD LOCK



SHELL SIZE

CONTACT ARRANGEMENT

09



2WK2 (MALE)



2WK2 (FEMALE)



2W2



5W1

15




3WK3 (FEMALE)



3WK3 (MALE)



3W3




7W2




11W1


25




5W5




9W4



13W3



17W2



21W1


37




8W8




13W6




17W5




25W3



27W2




21W4




7W7


50




24W7



36W4





43W2






47W1

Footprint (I)	J
9.4	2.54
7.2	2.84






SHELL 09










SHELL 15



SHELL 25



SHELL 37



SHELL 50

