






ELECTRICAL:

CURRENT RATING: 3A AC, DC
VOLTAGE RATING: 250V AC MAX.
OPERATING TEMPERATURE: -40 ° TO +85 °C
CONTACT RESISTANCE: 20 MILLIOHM MAX.
INSULATION RESISTANCE: 1000 MEGAOHM MIN.
VOLTAGE WITHSTANDING: 600V AC / MINUTE

MATERIAL:

CONTACT MATERIAL: COPPER ALLOY,
TIN OR GOLD PLATING OVER NICKEL
PLASTIC HOUSING: HIGH TEMP. THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0.

HOW TO ORDER:

W 0 1 9 - 0 8 0 1 - 2 X 1 - Z

OF CONTACTS:

02THRU12

PIN REMOVAL OPTION:

0 - FULLY LOADED

DEFINITION:

1-STRAIGHT
2-RIGHTANGLE

OPTION:

1 - PBT
2 - HIGH TEMP PLASTIC

**RoHS
COMPLIANT**

CONTACT PLATING

1-TIN PLATED
2-GOLDFLASH
3-10u"GOLD
5-30u"GOLD

Rev	Drawn	Checked	Approved	Date
0	WHS	S.M.	S.M.	4/21/06

SCALE: N/A

TOL. DEC. .X +/- 0.35 .XX +/- 0.25 .XXX +/- ANGLE +/- UNIT: mm

SMP TECHNOLOGY, INC.

HEADER; 2.54mm PITCH; 4 SIDES SHROUDED; MTA TYPE

8 PIN; FULLY LOADED

SERIES: W 0 1 9 - 0 8 0 1 - 2 X 1 - Z

Pg: 1