



Isometric View

DIMENSION(mm)

CONTACTS	A	B	C
2	3.00	6.85	7.20
3	6.00	9.85	10.20
4	9.00	12.85	13.20
5	12.00	15.85	16.20
6	15.00	18.85	19.20
7	18.00	21.85	22.20
8	21.00	24.85	25.20
9	24.00	27.85	28.20
10	27.00	30.85	31.20
11	30.00	33.85	34.20
12	33.00	36.85	37.20

HOW TO ORDER:

W 0 7 1 - X X 1 B - 1 5 0 0 - Z

SERIES: NUMBER OF CONTACTS: 02 Thru 12 RoHS COMPLIANT

ELECTRICAL :

CURRENT RATING: 5A AC/DC
DIELECTRIC WITHSTANDING VOLTAGE: 1500 AC / Minute
INSULATION RESESTANCE: 1000 Megohm Min.
TEMPERATURE RANGE: -40° C TO +105° C

MATERIAL :

MATERIAL: Nylon 66 UL 94V-0, Black

Rev	Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.
0	B.S.	S.M.	S.M.	11/14/12	
					Housing For Contacts; W071 Series,
					Single Row; Panel Mount without Ears
TOL. DEC. .X +/- 0.25 .XX +/- 0.15 .XXX +/- 0.05 ANGLE +/- 3° UNIT: mm / in SERIES: W 071-XX1B-1500-Z Pg: 1					